



Stainless Steel 2-Valve Instrument Manifold, 1/2 in. Female NPT, Ball Tip

Part #: SS-V2BF8

Specifications

Body Material 316 Stainless Steel

Connection 1 Size 1/2 in.

Connection 1 Type Female NPT

Connection 2 Size 1/2 in.

Connection 2 Type Female NPT

Maximum Temperature, °F (°C) 450 (232)

Minimum Temperature, °F (°C) -65 (-53)

eClass (4.1) 37010269

eClass (5.1.4) 37010269

eClass (6.0) 37010269

eClass (6.1) 37010269

eClass (10.1) 37010269

UNSPSC (4.03) 40141602

UNSPSC (10.0) 40141600

UNSPSC (11.0501) 40141600

UNSPSC (13.0601) 40141600

UNSPSC (15.1) 40141600

UNSPSC (17.1001) 40183103

Contact

If you have questions about this product, please contact your local authorized sales and service center. They can also tell you about supporting services to help you get the most out of your investment.

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.

Do not mix/interchange Swagelok products or components not governed by industrial design standards, including Swagelok tube fitting end connections, with those of other manufacturers.

2 Valve, Ball Stem

Provide fewer potential leak points while still meeting your liquid level or differential pressure application needs with the compact design of Swagelok manifolds which contain 2, 3 or 5 valves in a single body.



© 2026 Swagelok Company. All rights reserved.