

2200 Series / 2600 Series – General Purpose Industrial Pressure Transducers

- ▶ Gauge, Absolute, Vacuum and Compound Pressure Models Available
- ▶ Submersible, General Purpose and Wash Down Enclosures
- ▶ High Stability Achieved by CVD Sensing Element
- ▶ Millivolt, Voltage and Current Output Models

The 2200 series features stability and accuracy in a variety of enclosure options. The 2600 series extends the packaging options via an all welded stainless steel back end for demanding submersible and industrial applications. The 2200 and the 2600 feature proven CVD sensing technology, an ASIC (amplified units), and modular packaging to provide a sensor line that can easily accommodate specials while not sacrificing high performance.

Specifications

Input	
Pressure Range	Vacuum to 6000 psi (400 bar)
Proof Pressure	2 x Full Scale (FS) (1.5 x Fs for 400 bar, ≥ 5000 psi)
Burst Pressure	>35 x FS ≤ 100 psi (6 bar); >20 x FS ≥ 1000 psi (60 bar); >5 x FS ≤ 6000 psi (400 bar)
Fatigue Life	Designed for more than 100 million FS cycles
Performance	
Long Term Drift	0.2% FS/year (non-cumulative)
Accuracy	0.25 % FS typical (optional 0.15% FS)
Thermal Error	1.5% FS typical (optional 1% FS)
Compensated Temperatures	-5°F to +180°F (-20°C to +80°C)
Operating Temperatures	-40°F to +260°F (-40°C to +125°C) for elec. codes A, B, C, 1 -5°F to +180°F (-20°C to +80°C) for elec. codes 2, D, G, 3 -5°F to +125°F (-20°C to +50°C) for elec. codes F, M, P Amplified units >100°C maximum 24 VDC supply
Zero Tolerance	1% of span
Span Tolerance	1% of span
Response Time	0.5 ms
Mechanical Configuration	
Pressure Port	See ordering chart
Wetted Parts	17-4 PH Stainless Steel
Electrical Connection	See ordering chart
Enclosure	316 ss, 17-4 PH ss IP65 NEMA 4 for elec. codes A, B, C, D, G, 1, 2, 3 IP67 for elec. code "F" IP68 for elec. codes M, (max depth 200 meters H ₂ O) IP30 for elec. code "3" with flying leads
Vibration	70g, peak to peak sinusoidal, 5 to 2000 Hz (Random Vibration: 20 to 2000 Hz @ ≈20g Peak per MIL-STD.-810E Method 514.4)
Acceleration	100g steady acceleration in any direction 0.032% FS/g for 15 psi (1 bar) range decreasing logarithmically to 0.0007% FS/g for 6000 psi (400 bar) range.
Shock	20g, 11 ms, per MIL-STD.-810E Method 516.4 Procedure I
Approvals	CE, UR (22IC, 26IC, 22CS, 26CS)
Weight	Approx. 100 grams (additional cable; 75 g/m)

Series 2200



Series 2600




Individual Specifications

Millivolt Output units	
Output	100 mV (10 mv/v)
Supply Voltage (Vs)	10 VDC (15 VDC max.) Regulated
Bridge resistance	2600-6000 ohms
Voltage Output units	
Output	see ordering chart
Supply Voltage (Vs)	1.5 VDC above span to 35 VDC @ 6 mA
Supply Voltage Sensitivity	0.01% FS/Volt
Min. Load Resistance	(FS output / 2) Kohms
Current Consumption	approx 6 mA at 7.5V output
Current Output units	
Output	4-20 mA (2 wire)
Supply Voltage (Vs)	24 VDC, (7-35 VDC)
Supply Voltage Sensitivity	0.01% FS/Volt
Max. Loop Resistance	(Vs-7) x 50 ohms

Connection Code		mV units				Voltage units				Current units (4-20mA)		
		IN+	OUT+	OUT-	IN-	IN+	COM	OUT+	EARTH	(+)	(-)	EARTH
A, B, G	"DIN" PIN	1	2	3	E	1	2	3	4	1	2	4
C	"10-6 Bayonet" PIN	A	B	C	D	A	C	B	E	A	B	E
D	"cable"	R	Y	BL	G	R	BK	W	DRAIN	R	BK	DRAIN
F	"IP 67 cable"	R	Y	BL	G	R	BK	W	DRAIN	R	BK	DRAIN
M	"Immersible"	R	Y	BL	W	R	W	Y	DRAIN	R	BL	DRAIN
1	"8-4 Bayonet" PIN	A	B	C	D	A	C	B	D	A	B	D
2	"cable"	R	W	G	BK	R	BK	W	DRAIN	R	BK	DRAIN
3	"conduit & cable"	R	W	G	BK	R	BK	W	DRAIN	R	BK	DRAIN

Cable Legend:

R = Red
BL = Blue
BK = Black
W = White
Y = Yellow








PRESSURE TRANSDUCERS

Dimensions



2200 Series





Mini 4 Pin - No Connector
Code B



Mini 4 Pin - With Connector
Code A

IP67 Cable (Waterproof)
Code F

24 AWG Shielded PVC
IP65 or NEMA4 Cable
Code D or 2

24 AWG Shielded PVC

mV Gauge/Absolute Amplified Gauge

Amplified Absolute


Maximum diameter 1.07" (27.3 mm)

1/8-27 NPT
Code 08

1/4 - 18 NPT
Code 02 with snubber

Code 0J with snubber





1/4-18 NPT Internal
Code 0E

1/2-14 NPT
Code 0H

7/16-20 UNF-2A
Code 04

9/16-18 UNF-2A
Code 1P

G 1/8 Internal
Code 09



G 1/4 External
Code 01

R 1/4
Code 0A


2600 Series

10-6 or 8-4 Mil-C Connector
10-6 Code C


8-4 Code 1

Large DIN 43650 Plug
Code G

Conduit Connector with Cable
Code 3

24 AWG Shielded PVC
Conduit Connector with Flying Leads
Code 3

with length "U"
Moulded, Immersible Cable
Code M

24 AWG, Vent, Shielded, Polyurethane

mV Gauge/Absolute Amplified Gauge

Amplified Absolute


Maximum diameter 1.07" (27.3 mm)

Nose Cone - Black Acetal
Code 19

Nose Cone Sink Weight

Code 29

inch
mm

How to Order

Use the **bold** characters from the chart below to construct a product code

Series **2200** **2600**

Output
A - 100 mV **C** - 1-6V **J** - 0.5-5.5V **G** - 0.2-10.2V
B - 4-20mA **D** - 1-11V **R** - 0-5V **F** - 0.1-5.1V
H - 1-5V **S** - 0-10V

Pressure Datum
A* - Absolute **G** - Gauge
 *Max absolute range is 25 bar. (≤ 300 psi)

Pressure Range³ – psi
F07 - 0-7.5 **G60** - 0-600 **Vac** = -15 psi
F15 - 0-15 **H10** - 0-1,000 **1F5** - Vac-0
F30 - 0-30 **H15** - 0-1,500 **3F0** - Vac-15
F60 - 0-60 **H20** - 0-2,000 **6F0** - Vac-45
G10 - 0-100 **H30** - 0-3,000 **1G0** - Vac-85
G15 - 0-150 **H40** - 0-4,000 **1G5** - Vac-135
G20 - 0-200 **H50** - 0-5,000 **2G0** - Vac-185
G30 - 0-300 **H60** - 0-6,000 **3G0** - Vac-285
G50 - 0-500

Pressure Range - bar
A10 - 0-1 **B25** - 0-25 **Vac** = -1 bar
A16 - 0-1.6 **B40** - 0-40 **1A0** - Vac-0
A25 - 0-2.5 **B60** - 0-60 **1A6** - Vac-0.6
A40 - 0-4 **C10** - 0-100 **2A5** - Vac-1.5
A60 - 0-6 **C16** - 0-160 **4A0** - Vac-3
B10 - 0-10 **C25** - 0-250 **6A0** - Vac-5
B16 - 0-16 **C40** - 0-400 **1B0** - Vac-9
1B6 - Vac-15
2B5 - Vac-24
4B0 - Vac-39

Pressure Port
08 - 1/8-27 NPT External
02 - 1/4-18 NPT External
0J - 1/4 NPT External w/snubber
0E - 1/4 NPT Internal
0H - 1/2-14 NPT External
04 - 7/16-20 External (SAE #4, J514)
1P - 9/16-18 External (SAE #6, J1926-2)
1J - 7/16-20 External (SAE #4, J1926-2)

European Threads
09 - G1/8 Internal
01 - G1/4 External
0A - R1/4 External
 Submersible (2600 only)
19 - Plastic Nose Cone
29 - Sink Weight Nose Cone

Performance Code
 Accuracy/Thermal
A - .25%/1.5%
B - .15%/1.0%

Cable Length¹
U - No Cable Fitted^{1 2}
D - 1 Metre (3 feet)
E - 3 Metres (9 feet)
F - 5 Metres (16 feet)
G - 10 Metres (32 feet)

Apparatus Protection
2 - mV Only Transient Protection CE Mark, UR
3 - Amplified Only RFI Protected CE Mark, UR

Electrical Connection (See Notes)
 2200 Series
A - 4 PIN DIN (Micro) Mating Connector Supplied
B - 4 PIN DIN (Micro) Mating Connector Not Supplied
2 - Cable Nema 4 USA
D - Cable European Color Code
F - Cable Gland Metal IP67
 2600 Series
C - Fixed Plug Size 10-6 Mating Plug Not Supplied
G - Fixed Plug To DIN 43650 Mating Plug Supplied
M - Moulded Cable Immersible
1 - Fixed Plug Size 8-4 Mating Plug Not Supplied
3 - Conduit Connector 1/2NPT Ext. 1M Cable²

Notes:
 1. When electrical connection is cable please select a cable length from Table 1 below. When electrical connection is DIN or plug style "U" must be specified.
 2. Where electrical connection -3 and cable length -U occur in part number, the unit will be supplied with flying leads (4-1/2" IP30).
 3. Additional Pressure Ranges are available. Please consult factory.



Table 1 - Cable Length

(2600 Series) (2200 Series select "U" through "G")

Code	Length (M)	Code	Length (M)
U	No Cable Fitted	M	40
D	1	N	50
E	3	P	75
F	5	Q	100
G	10	R	125
H	15	S	150
J	20	4	170
K	25	5	200
L	30	6	225

Note: Maximum cable length on a 2200 is 10 metres.